# HP U27 4K Wireless Monitor



# Seamless connection, beautifully uncluttered.

Experience 4K<sup>1</sup> resolution with a wireless sharing PC monitor that's built for both work and play. With reduced latency, you'll complete tasks with ease and stream picture perfect content. Now you can enjoy the freedom to connect to your PC wirelessly, or wired. And with 4K resolution, an adjustable stand, and excellent down firing speakers -- get ready for quality like you've never seen.



### 4K resolution. Wireless work and play solution.

Experience a 4K<sup>1</sup> wireless sharing PC monitor that's perfect for both work and play. With reduced latency, you'll wirelessly complete tasks with ease and stream<sup>2</sup> picture perfect content.

### Clutter free connectivity.

Enjoy the freedom to connect wirelessly or wired using the monitor that's designed for convenience. Now you can seamlessly share photos, videos and more, clutter free. Connect from your laptop when you need to work, or when you're ready to  $play^3$ .

### Revolutionary experience. Unbelievable quality.

Elevate your viewing experience with the 27in 4K<sup>1</sup> wireless monitor that's designed to delight. With 3-sided borderless bezels, Wi-fi direct connect™, IPS technology, height adjustable stand, and excellent down firing speakers, enjoy quality like you've never seen.

<sup>1</sup> 4K content required to view full 4K images. <sup>2</sup> Based on all 4K PC wireless integrated desktop displays in the market as of (date). Testing based on video streaming via Wi-Fi direct using a device with a wireless card. 4K sharing minimum system requirements are Windows 10 1809 or later, Wi-Fi 802.11 ac, i5 processor or greater, 8GB RAM or greater. <sup>3</sup> Internet service required and not included.

# HP U27 4K Wireless Monitor

# Featuring

#### Ultra High Definition 4K

Experience cinematic quality with the incredible definition of 4K. Visuals this impressive are simply unforgettable.

#### Step up to the best

IPS technology brings you clear views from almost any angle. Every seat is the best seat in the house.

#### Virtually Edge to Edge Panel

Expansive is the only way to describe the maximized screen area you get with the beautiful edge-to-edge glass panel.

#### Compact, sleek design

Get everything you need in one elegant package. Just one connection to the wall eliminates cable clutter. Slim design gives you more room for an enhanced computing experience.

#### Micro-edge display

With virtually no bezel encircling the display, an ultra-wide viewing experience provides for seamless multi-monitor set-ups.

## AMD<sup>®</sup> FreeSync<sup>™</sup> technology

See and feel the difference of fluid, responsive gameplay. By synchronizing the refresh rate with your GPU, AMD® FreeSync™ makes display stutter, input lag, and screen tears ancient history.

#### Seamless visuals

Videos and games come to life with less stutter or blur for more realistic play with smooth 5-millisecond gray-to-gray response time.

#### Extreme detail

Amazing clarity is delivered by 10,000,000:1 dynamic contrast ratio for deeper blacks, brighter whites, and crisper colors.

#### Share the panoramic view

Vibrant detail from practically any position with consistent color and image clarity maintained across ultra-wide 178-degree horizontal and vertical viewing angles.

#### Highly accurate color

With more than 99% sRGB color space, this HP display provides ideal color reproduction with minimal effort. Perfect for photos, videos—all your creative projects.

#### Anti-glare panel

Enjoy the sun and your favorite content with this anti-glare panel. Non-reflective and low-gloss, you'll get less glare while you're outside.

#### Low blue light

Using the Low Blue Light mode subtly shifts your display's colors to a warmer spectrum, while making whites more natural and putting less strain on your eyes.

4K content required to view full 4K images

<sup>&</sup>lt;sup>2</sup> FreeSync™ is only available when it is connected on DisplayPort™ or HDMI. FreeSync is an AMD® technology enabled on FHD or QHD displays and is designed to eliminate stuttering and/or tearing in games and videos by Icking a display's refresh rate to the frame rate of the graphics card. AMD Radeon Graphics and/or AMD A-Series APU-compliant monitors with DisplayPort/HDMI Adaptive Commised and the refresh rate vary by monitor. More information is available at www.amd.com/freesync. <sup>3</sup> All performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary, either higher or lower.

# HP U27 4K Wireless Monitor







Technology Bac     16.9       Dipplay type     IP5       Read plath     0.155 mm       Horizontal Versing angle     178°       Tit     -5 to +16°       Height adjustment range     100 mm       Response time     5 ms GG (with overdived)       Brightness     300 nls       Contrast ratio     1000:1 static       Resonneutine     1002:1 static       Display scan frequency (horizontal)     31-135 KHz       Display scan frequency (ho	Display size	27"
Display type     IPS       Pixed pitch     0.155 mm       Horizontal viewing angle     1728*       Tit     -5 to +16*       Height dajustment range     100 mm       Response time     5ms GG (with overdrive)       Brightness     300 nts       Contrast ratio     1000 ml       Response time     5ms GG (with overdrive)       Brightness     300 nts       Contrast ratio     1000 rs state:       Recommended resolution     4K UHD (3840 x 2160 @ 60 Hz)       Resolution maximum     KUHD (3840 x 2160 @ 60 Hz)       Resolution supported     1024 x 768; 1200 x 1020; 1200 x 800; 1440 x 900; 1600 x 900; 1600 x 1050; 1920 x 1080; 1920 x 1000; 1920 x 100		
Preside     0.155 mm       Horizontal weiwing angle     178*       Tilk     ~5 to +16*       Height adjustment range     100 mm       Response time     5m 6/G (with overdrive)       Brightness     300 nits       Contrast ratio     1000/mm       Resource time     5m 6/G (with overdrive)       Brightness     300 nits       Contrast ratio     1000/mm       Resolution (maximum)     4K UHD (3840 x 2160 @ 60 Hz)       Resolutions supported     1024 x 78:12 abx 1024; 1280 x 201; 1280 x 800; 1440 x 900; 1600 x 900; 1680 x 1050; 1920 x 1080; 1920 x 1200; 3840 x 2160; 640 x 480; 640 x 480; 640 x 490; 1280 x 100; 1920 x 1080; 1920 x 1200; 3840 x 2160; 640 x 480; 660 x 600; 720 x 700       Display scn frequency thorizontal)     31-135 KHz       Displays can frequency thorizontal)     31-135 KHz       Displays can frequency thorizontal)     40-60 Hz       Display scn frequency thorizontal)     40-50 Hz       Display scn frequency thorizontal)     40-60 Hz       Display scn frequency thorizontal)     40-60 Hz       Display scn frequency thorizontal)     40-60 Hz       Display scn frequency thorizontal     40-60 Hz       Display Stase Control Options	· · · · · · · · · · · · · · · · · · ·	
Horizontal viewing angle   178'     Tit   -5 to +16'     Height adjustment range   100 mm     Response time   5ms GtG (with overdrive)     Brightness   200 nits     Contrast ratio   1000:1 static     Recommended resolution   4K UHD (3840 x 2160 @ 60 Hz)     Resolution (maximum)   4K UHD (3840 x 2160 @ 60 Hz)     Resolution supported   1024 x 768; 1200 x 1024; 1280 x 720; 1280 x 800; 1440 x 900; 1680 x 1050; 1920 x 1080; 1920 x 1280; 3840 x 2160; 640 x 480; 820 x 500; 220 x 700;     Display scan frequency (writzontal)   31-13; 5KHz     Display scan frequency (writzontal)   41-13; 5KHz     Display scan frequency (writzontal)   41-13; 5KHz     Display scan frequency (writzontal)   41-13; 5KHz     Display input Type   1 DisplayPort** 1, 2, 1 HDM (with HDCP support); 3 USP-3, 3, 2 Gm 1     Physical security features   Security lock-ready     Energy efficiency   Energy efficiency class; B;     Display User Control Options   Brightness; Color control: Contrast; Exit; Image control; Information; Language; Management; Power control; Input control; Menu control     Addi port   1 Headphone Out Combo Jack     Product dimensions   61,35 x 15,3 x 13,3 x 13,10 m. Wtm stand     61,35 x 15,3 x 14		
Height adjustment range   100 mm     Response time   Sms GiG (with overdrive)     Brightness   300 nits     Contrast ratio   1000:11 static     Recommended resolution   4K UHD (3840 x 2160 (0 60 Hz)     Resolution (maximum)   4K UHD (3840 x 2160 (0 60 Hz)     Resolution (maximum)   4K UHD (3840 x 2160 (0 60 Hz)     Resolution supported   1024 x 768; 1280 x 1024; 1280 x 720; 1280 x 800; 1440 x 900; 1600 x 900; 1680 x 1050; 1920 x 1080; 1920 x 1280; 3840 x 2160; 640 x 480; 390 x 360; 720 x 700     Display scan frequency (horizontal)   31-13 S Kliz     Display scan frequency (vertical)   40-60 Hz     Display scan frequency   Encryy efficiency class B;     Display Scan frequency   Encryy efficiency class B;     Display Scan frequency   Encryy efficiency class B;     Display Scan frequency   Encry efficiency class B;     Display Scan frequency   Encry efficiency class B;     Display Scan frequenchacuto	Horizontal viewing angle	178°
Response time Sms GLG (with overdrive)   Brightness 300 ntis   Contrast ratio 1000:1 static   Recommender resolution AK UHD (3840 x 2160 @ 60 Hz)   Resolution (maximum) 4K UHD (3840 x 2160 @ 60 Hz)   Resolution finaximum) 4K UHD (3840 x 1260 @ 60 Hz)   Resolution supported 1024 x 766; 1280 x 1024; 1280 x 720; 1280 x 800; 1440 x 900; 1600 x 900; 1680 x 1050; 1920 x 1200; 1920 x 1200; 3840 x 2160; 640 x 480; 800 x 800; 720 x 700   Display scan frequency (horizontal) 31-135 KHz   Display User Control Options AMD FreeSync <sup>(H)</sup> Low blue light mode: Anti-glare   Display User Control Options Brightency display forth "1.2; 1 HDMI (with HDEP support); 3 USB-4.3.2 Gen 1   Product dimensions Brightency displas for List mits and Prazies (60 Hz); 120 x 402 (cm bits and Prazies (60 Hz); 120 x 402 (cm bits and Prazies (60 Hz); 120 x 402 (cm bits and Prazies (60 Hz); 120 x 402 (cm bits and Prazies (for Hz); 110 Hits stand Prazies (for Hz); 120 x 402 (cm Hz); 140 x 400 (cm bits and Prazies (for Hz); 140 x 400 (c	Tilt	-5 to +16°
Bightness   300 nits     Contrast ratio   10001 static     Recommended resolution   4K UHD (3840 x 2160 @ 60 Hz)     Resolution (maximum)   4K UHD (3840 x 2160 @ 60 Hz)     Resolution supported   1024 x 768; 1280 x 1024; 1280 x 720; 1280 x 800; 1440 x 900; 1600 x 900; 1560 x 1050; 1920 x 1200; 3840 x 2160; 640 x 480; 720 x 700     Display scan frequency (horizontal)   31:135 KHz     Display scan frequency (vertical)   40:600 Hz     Display features   AMD FreeSync <sup>m</sup> : Low blue light mode; Anti-glare     Display leatures   AMD FreeSync <sup>m</sup> : Low blue light mode; Anti-glare     Display leatures   Security lock-ready     Energy efficiency   Energy efficiency class: B;     Display User Control Options   Brightness; Color control; Contrast; Exit; Image control; Information; Language; Management; Power control; Input control; Menu control     Audig port   1 Headphone Out Combo Jack     Product dimensions   61.35 x 19.27 & 810 B     105/s1 y 124 x 128 x 92 x 18.19 in   24.15 x 26.28 x 18.419 in     Operating temperature range   51 to 55°;     Operating temperature range   51 to 55°;     Operating temperature range   24 to 5 x 26 x 18.419 in     Questing temperature range   10 to 55°;     O	Height adjustment range	100 mm
Contrast ratio     1000:1 static       Recommended resolution     4K UHD (3840 x 2160 @ 60 Hz)       Resolution (maximum)     4K UHD (3840 x 2160 @ 60 Hz)       Resolution supported     1024 x 766 : 786 : 102 n (1261 ; 1280 x 720; 1280 x 800; 1440 x 900; 1600 x 900; 1680 x 1050; 1920 x 1200; 3840 x 2160; 640 x 480; 800 x 600; 720 x 700       Display scan frequency (vertical)     31-13 S Kiz     Display scan frequency (vertical)     40-60 Hz       Display scan frequency (vertical)     40-60 Hz     Display forth     1.2; 1 HOMI (with HDCP support), 3 USB-A 3.2 Gen 1       Physical security features     Security lock-ready     Energy efficiency (locy class: B;     Display forth     1.2; 1 HOMI (with HDCP support), 3 USB-A 3.2 Gen 1       Physical security features     Security lock-ready     Energy efficiency class: B;     Energy efficiency class: B;       Display User Control Options     Brightness; Color control: Contrast; Exit; Image control; Information; Language; Management; Power control; Input control; Menu control: And 0 port     1 Headphone Out Combo Jack       Product dimensions     24, 15 x 5, 32 x 6, 6 cm     24, 15 x 7, 62 x 19 J an     24, 15 x 7, 62 x 19 J an       Weight     5 kit; Packed: 7, 64 z lb     0     0     0     0     0       Operating temperature range     5 to 35°C	Response time	5ms GtG (with overdrive)
Recommended resolution     4K UHD (3840 x 2160 @ 60 Hz)       Resolution (maximum)     4K UHD (3840 x 2160 @ 60 Hz)       Resolutions supported     1024 x 766; 1280 x 1024; 1280 x 720; 1280 x 800; 1440 x 900; 1600 x 900; 1920 x 1080; 1920 x 1200; 3840 x 2160; 640 x 480; 600 x 500; 720 x 700       Display scan frequency (horizontal)     31-135 KHz       Display scan frequency (horizontal)     31-135 KHz       Display scan frequency (horizontal)     31-135 KHz       Display features     AMD FreeSynct**: Low blue light mode; Anti-glare       Display perfit     12; 1 HDM (with HDCP support); 3 USE-A 3.2 Gen 1       Physical security features     Security lock-ready       Energy efficiency     Energy efficiency class: B;       Display Dust     Energy of Compo Lack       Audio port     1 Headphone Out Combo Jack       Product dimensions     24:15 2:3 52 2:3 66 2 cm       Product dimensions     Sig: Packed: 15.4 2; Bin 30       Weight     Sig: Packed: 15.4 2; Bin 30       Operating temperature range     41 to 95°F       Operating temperature range     41 to 95°F       Operating turner and class in the box     Monitor: ECC; CS; CS; CS; CS; CS; CS; CS; CS; CS;	Brightness	300 nits
Resolution (maximum)   4K UHD (3840 x 2160 @ 60 Hz)     Resolutions supported   1024 x 76g; 1280 x 1024; 1280 x 720; 1280 x 800; 1440 x 900; 1600 x 900; 1680 x 1050; 1920 x 1080; 1920 x 1200; 3840 x 2160; 640 x 480; 800 x 600; 720 x 700     Display scan frequency (horizontal)   31-135 KHz     Display scan frequency (horizontal)   40-60 Hz     Display input Type   10 biplay free Twices     AMD FreeSync <sup>HE</sup> : Low blue light mode; Anti-glare     Display input Type   10 biplay Port* 1.2; 11 HDMI (with HDCP support); 3 USB-A 3.2 Gen 1     Physical security features   Security lock-ready     Energy efficiency   Energy efficiency (lass: B;     Display User Control Options   Brightness; Color control; Contrast; Exit; Image control; Information; Language; Management; Power control; Input control; Menu control     Audio port   1 Headphone Out Combo Jack     0133 x 193 3 x 30.13 cm With stand   Product dimensions     24.15 x 1.62 x 10.3 k 2.9 x 14.3 H   24.15 x 1.62 x 10.3 Cm     0perating temperature range   5 to 35°C     Operating temperature range   110 55°F	Contrast ratio	1000:1 static
Resolutions supported   1024 x 768; 1280 x 1024; 1280 x 720; 1280 x 800; 1440 x 900; 1600 x 900; 1680 x 1050; 1920 x 1080; 1920 x 1200; 3840 x 2160; 640 x 480; 800 x 600; 720 x 700     Display scan frequency (horizontal)   31-135 KHz     Display scan frequency (vertical)   40-60 Hz     Display features   AMD FreeSync <sup>m</sup> ; Low blue light mode; Anti-glare     Display features   AMD FreeSync <sup>m</sup> ; Low blue light mode; Anti-glare     Display features   Security lock-ready     Energy efficiency   Energy efficiency class; B;     Display lay User Control Options   Brightness; Color control; Contrast; Exit; Image control; Information; Language; Management; Power control; Input control; Menu control     Audio port   1 Headphone Out Combo Jack     Product dimensions   61.35 x 5.32 x 36.65 cm 61.35 x 13.35 x 40.2 cm 24.16 x 2.09 x 14.43 in 24.15 x 7.62 x 19.7 in With stand Packet 27.52 x 4.92 x 18.19 in     Weight   5 kg Packet 7.45 k dg 11.05 lb; Packet 16.42 lb     Operating temperature range   5 to 35°C     Operating temperature range   20 to 80% RH     Certifications and compliances   BisNi; CE; CC; CE; CS; CS; NENT; EAC; EUP Lot-5; FCC; GEMS; HRN N N0.201; ICES; IS 1121; KC/KCC; PSB; RCM; SABS IEC 60950-1; SAS0; TUV Bauat; VCC; B; EUP Lot 26; EUP Lot 26; EUP Lot 26; EC 60950:1; 999; eStandby; MEPS (HP) UKRAINA; ISD 9241; China CEL     Power supply   Input voltage 100 to 240 VAC	Recommended resolution	4K UHD (3840 x 2160 @ 60 Hz)
Restutions supported480, 800 x 600, 720 x 700Display scan frequency (borizontal)31-135 KHzDisplay scan frequency (vertical)40-60 HzDisplay featuresAMD FreeSync <sup>19</sup> , Low blue light mode; Anti-glareDisplay featuresAMD FreeSync <sup>19</sup> , Low blue light mode; Anti-glareDisplay featuresSecurity lock-readyPhysical security featuresSecurity lock-readyEnergy efficiencyEnergy efficiency class: B;Display User Control OptionsBrightness; Color control; Contrast; Exit; Image control; Information; Language; Management; Power control; Input control; Menu controlAudio port1 Headphone Out Combo JackProduct dimensions61.35 x 53.23 x 56.5 cm 61.35 x 7.62 x 19.7 in With stand Packet 27.52 x 4.92 x 18.19 inWeight5 kc; Packet?, r 64 kg 11.05 lb; Packet? 16 kg 20 x 14.43 in 24.16 x 2.09 x 14.43 in 	Resolution (maximum)	4K UHD (3840 x 2160 @ 60 Hz)
Display scan frequency (vertical)   40-60 Hz     Display features   AMD FreeSync <sup>™</sup> ; Low blue light mode; Anti-glare     Display input Type   1 DisplayPort <sup>™</sup> 1.2; 1 HDMI (with HDCP support); 3 USB-A 3.2 Gen 1     Physical security features   Security lock-ready     Energy efficiency   Energy efficiency class: B;     Display User Control Options   Brightness; Color control; Controat; Exit; Image control; Information; Language; Management; Power control; Input control; Menu control     Audio port   1 Headphone Out Combo Jack     61.35 x 13.25 x 50.32 r 36.65 rm   61.35 x 13.25 x 50.32 r rm. With stand     Product dimensions   24,16 x 2.05 x 14.43 lm     24,16 x 2.05 x 14.43 lm   24,16 x 2.05 x 14.43 lm     Veight   5 kcg. Packed: 7.45 kg     11.05 lb; Packed: 16.42 lb   Doperating temperature range     Operating temperature range   20 to 80% RH     Certifications and compliances   BSMI; CB; CCC; CC; CSA; CSA-NRTL; EAC; EUP Lot-6; FCC; GEMS; HRN N N0.201; ICES; IS 1121; KC/KCC; PSB; RCM; SABS IEC 60950-1; SAS0; TUV     Boardt U voltage 100 to 240 VAC   Warranty     Vear parts and labour limited warranty.   What's in the box     Monitor; HDMI cable; Warranty, card; Power cable   VESA mount     Product number   9TQ13AS	Resolutions supported	
Display features   AMD FreeSync <sup>™</sup> ; Low blue light mode; Anti-glare     Display Input Type   1 DisplayPort <sup>™</sup> 1.2; 1 HDMI (with HDCP support); 3 USB-A 3.2 Gen 1     Physical security features   Security lock-ready     Energy efficiency   Energy efficiency class: B;     Display User Control Options   Brightness; Color control; Contrast; Exit; Image control; Information; Language; Management; Power control; Input control; Menu control     Audio port   1 Headphone Out Combo Jack     Product dimensions   61.35 x 53.2 x 36.65 cm 61.35 x 53.2 x 46.62 cm 24.16 x 2.05 x 14.43 in 24.15 x 7.62 x 19.7 id. with stand Packed: 27.5 x 4.9 z X 14.9 in 24.15 x 7.62 x 19.7 id. with stand Packed: 27.5 x 4.9 z X 14.9 in 24.15 x 7.62 x 19.7 id. with stand Packed: 27.5 x 4.9 z X 19.9 in     Weight   5 kcg: Packed: 7.45 kg 11.05 lb; Packed: 16.42 lb   Doperating temperature range   5 to 35°C     Operating temperature range   5 to 35°C   Desplay: ICC; CE; CSA: CSA-NRTL; EAC; EUP Lot-6; FCC; GEMS; HRN N N0.201; ICES; IS 1121; KC/KCC; PSB; RCM; SABS IEC 60950-1; SASO; TUV Bauart; VCC; ISC; EUP Lot-26; IEC 60950: 1999; estandby; MEPS (HP) UKRAINIA; ISO 9241; China CEL     Power supply   Input voltage 100 to 240 VAC     Waranty   1 year parts and labour limited waranty.     What's in the box   Monitor; HDMI cable; Warranty card; Power adapter; QSP; AC power cable     VESA mount   100 mm x 100 mm (bracket included)     Pro	Display scan frequency (horizontal)	31-135 KHz
Display Input Type   1 DisplayPort™ 1.2; 1 HDMI (with HDCP support); 3 USB-A 3.2 Gen 1     Physical security features   Security lock-ready     Energy efficiency   Energy efficiency class: B;     Display User Control Options   Brightness; Color control; Contrast; Exit; Image control; Information; Language; Management; Power control; Input control; Menu control     Audio port   1 Headphone Out Combo Jack     61.35 x 93.35 x 50.13 cm With stand     Product dimensions   24.15 x 7.95 x 50.13 cm With stand     Packed: 69.9 x 12 5 x 46.2 cm     24.15 x 7.95 x 50.13 cm With stand     Packed: 69.9 x 12 5 x 46.2 cm     24.15 x 7.95 x 50.13 cm With stand     Packed: 15.4 Y 13.35 x 10.3 cm     24.15 x 7.95 x 4.92 x 18.19 in     Weight   5 kg; Packed: 7.45 kg     11.05 lb; Packed: 16.42 lb     Operating temperature range   5 to 35°C     Operating temperature range   2 to 80% RH     Certifications and compliances   BSMI; CE; CC; CE; CSA; CSA-NRTL; EAC; EUP Lot-6; FCC; GEMS; HRN N N0.201; ICES; IS 1121; KC/KCC; PSB; RCM; SABS IEC 60950-1; SASO; TUV     Bawart; VCC; ISC; EUP Lot-25; IEC 60950:1999; estandby; MEPS (HP) UKRAINA; ISO 9241; China CEL     Power supply   Input voltage 100 to 240 VAC     Warranty   1 year parts and labour limited warranty. <th>Display scan frequency (vertical)</th> <th>40-60 Hz</th>	Display scan frequency (vertical)	40-60 Hz
Physical security features     Security lock-ready       Energy efficiency     Energy efficiency (dass: B;       Display User Control Options     Brightness; Color control; Contrast; Exit; Image control; Information; Language; Management; Power control; Input control; Menu control       Audio port     1 Headphone Out Combo Jack       61:35 x 5:32 x 36.65 cm     61:35 x 5:32 x 36.65 cm       61:35 x 19:35 x 5:01 37 m With stand     Packed: 69:9 x 12.5 x 46.2 cm       24:15 x 7.62 x 19:24 in     24:15 x 7.62 x 19:24 in       24:15 x 7.62 x 19:24 in     24:15 x 7.62 x 19:24 in       Velight     5 kg: Packed: 7.45 kg       11:05 lb; Packed: 16:42 lb     0       Operating temperature range     5 to 35°C       Operating temperature range     20 to 80% RH       Certifications and compliances     BSMI; CB; CC; CE; CSA; CSA-NRTL; EAC; EUP Lot-6; FCC; GEMS; HRN N N0.201; ICES; IS 1121; KC/KCC; PSB; RCM; SABS IEC 60950-1; SAS0; TUV       Bauart; VCC; ISC; EUP Lot-26; IEC 60950:1999; eStandby; MEPS (HP) UKRAINIA; ISO 9241; China CEL       Power supply     Input voltage 100 to 240 VAC       Warranty     1 year parts and labour limited warranty.       What's in the box     Monitor; HDMI cable; Warranty card; Power adapter; QSP; AC power cable       VESA mount     100 mm x 100 mm (brack	Display features	AMD FreeSync™; Low blue light mode; Anti-glare
Energy efficiencyEnergy efficiency class: B;Display User Control OptionsBrightness; Color control; Contrast; Exit; Image control; Information; Language; Management; Power control; Input control; Menu controlAudio port1 Headphone Out Combo JackProduct dimensions $61.35 \times 5.32 \times 36.65 \text{ cm} \\ 61.35 \times 19.35 \times 50.13 \text{ cm}$ With stand Packed: 69.91 × 12.5 × A6.2 cm 24.16 × 2.09 × 12.6 × A6.2 cm 24.16 × 2.09 × 12.6 × A6.2 cm 24.16 × 2.09 × 14.43 in 24.15 × 7.62 × 19.74 in With stand Packed: 69.91 × 12.5 × A6.2 cm 24.16 × 2.09 × 14.43 in 24.15 × 7.62 × 19.74 in With stand Packed: 61.91 in With stand Packed: 61.91 in With stand Packed: 61.91 in With stand Packed: 61.92 × 18.19 inWeight5 kg; Packed: 7.45 kg 11.05 lb; Packed: 16.42 lbOperating temperature range5 to 35°COperating temperature range20 to 80% RHCertifications and compliancesBSM; CCC, CE; CSA; CSA-NRTL; EAC; EUP Lot-6; FCC; GEMS; HRN N N0.201; ICES; IS 1121; KC/KCC; PSB; RCM; SABS IEC 60950-1; SASO; TUV Bauart; VCC; ISC; EUP Lot-26; IEC 60950: 1999; estandby; MEPS (HP) UKRAINIA; ISO 9241; China CELPower supplyInput voltage 100 to 240 VACWarranty1 year parts and labour limited warranty.What's in the boxMonitor; HDMI cable; Warranty card; Power adapter; QSP; AC power cableVESA mount100 mm x 100 mm (bracket included)Product number9TQ13AS	Display Input Type	1 DisplayPort™ 1.2; 1 HDMI (with HDCP support); 3 USB-A 3.2 Gen 1
Display User Control Options   Brightness; Color control; Contrast; Exit; Image control; Information; Language; Management; Power control; Input control; Menu control     Audio port   1 Headphone Out Combo Jack     Product dimensions   61.35 x 5.32 x 36.65 cm 61.35 x 19.35 x 50.13 cm With stand Packet: 60.9 x 12.5 x 46.2 cm 24.15 x 7.62 x 19.74 in With stand Packet: 7.52 x 4.92 x 18.19 in     Weight   5 kg; Packet: 7.45 kg 11.05 lb; Packet: 16.42 lb     Operating temperature range   5 to 35°C     Operating temperature range   20 to 80% RH     Certifications and compliances   BSMI; CC; CE; CSA: CSA-NRTL; EAC; EUP Lot-6; FCC; GEMS; HRN N N0.201; ICES; IS 1121; KC/KCC; PSB; RCM; SABS IEC 60950-1; SAS0; TUV Bauart; VCC; ISC; EUP Lot-26; IEC 60950:1999; estandby; MEPS (HP) UKRAINIA; ISO 9241; China CEL     Power supply   Input voltage 100 to 240 VAC     Warranty   1 year parts and labour limited warranty.     What's in the box   Monitor; HDMI cable; Warranty card; Power adapter; QSP; AC power cable     VESA mount   100 mm x 100 mm (bracket included)     Product number   9TQ13AS	Physical security features	Security lock-ready
Audio port1 Headphone Out Combo JackAudio port1 Headphone Out Combo Jack61.35 x 5.32 x 36.65 cm61.35 x 19.35 x 50.13 cm With stand Packed: 69.9 x 12.5 x 46.2 cm 24.15 x 2.09 x 14.43 in 24.15 x 52 x 4.92 x 18.19 inWeight5 kg: Packed: 7.45 kg 11.05 lb; Packed: 16.42 lbOperating temperature range5 to 35°COperating temperature range20 to 80% RHCertifications and compliancesBSMI; CB; CCC; CE; CSA; CSA-NRTL; EAC; EUP Lot-6; FCC; GEMS; HRN N N0.201; ICES; IS 1121; KC/KCC; PSB; RCM; SABS IEC 60950-1; SAS0; TUV Bauart; VCCI; ISC; EUP Lot-25; IEC 60950: 1999; eStandby; MEPS (HP) UKRAINIA; ISO 9241; China CELPower supplyInput voltage 100 to 240 VACWarranty1 year parts and labour limited warranty.What's in the boxMonitor; HDMI cable; Warranty card; Power adapter; QSP; AC power cableVESA mount100 mm x 100 mm (bracket included)Product number9TQ13AS	Energy efficiency	Energy efficiency class: B;
Product dimensions      61.35 × 5.32 × 36.65 cm 61.35 × 19.35 × 50.13 cm With stand Packed: 69.9 × 12.5 × 46.2 cm 24.15 × 7.62 × 19.74 in With stand Packed: 7.43 in 24.15 × 7.62 × 19.74 in With stand Packed: 7.752 × 4.92 × 18.19 in Packed: 7.752 × 4.92 × 18.19 in Step: Packed: 7.45 kg 11.05 lb; Packed: 7.45 kg 11.05 lb; Packed: 16.42 lb Operating temperature range S to 35°C Operating temperature range 20 to 80% RH Certifications and compliances BSMI; CB; CCC; CE; CSA; CSA-NRTL; EAC; EUP Lot-6; FCC; GEMS; HRN N N0.201; ICES; IS 1121; KC/KCC; PSB; RCM; SABS IEC 60950-1; SAS0; TUV Bauart; VCC; ISC; EUP Lot-26; IEC 60950:1999; eStandby; MEPS (HP) UKRAINIA; ISO 9241; China CEL Power supply Input voltage 100 to 240 VAC Warranty 1 year parts and labour limited warranty. What's in the box Monitor; HDMI cable; Warranty card; Power adapter; QSP; AC power cable VESA mount 100 mm x 100 mm (bracket included) Product number 9TQ13AS 	Display User Control Options	Brightness; Color control; Contrast; Exit; Image control; Information; Language; Management; Power control; Input control; Menu control
Product dimensions      61.35 x 19.35 x 50.13 cm With stand Packed: 69.9 x 12.5 x 46.2 cm 24.16 x 2.09 x 14.43 in 24.15 x 7.62 x 19.74 in With stand Packed: 27.52 x 4.92 x 18.19 in Packed: 27.52 x 4.92 x 18.19 in Stg; Packed: 7.45 kg 11.05 tb; Packed: 16.42 lb Operating temperature range St to 35°C Operating temperature range 20 to 80% RH Certifications and compliances BSMI; CB; CCC; CE; CSA; CSA-NRTL; EAC; EUP Lot-6; FCC; GEMS; HRN N N0.201; ICES; IS 1121; KC/KCC; PSB; RCM; SABS IEC 60950-1; SAS0; TUV Baurt; VCC; ISC; EUP Lot-26; IEC 60950:1999; eStandby; MEPS (HP) UKRAINIA; ISO 9241; China CEL Power supply Input voltage 100 to 240 VAC Warranty 1 year parts and labour limited warranty.What's in the box Monitor; HDMI cable; Warranty card; Power adapter; QSP; AC power cable VESA mount 100 mm x 100 mm (bracket included) Product number 9TQ13AS Paula S	Audio port	1 Headphone Out Combo Jack
weight11.05 lb; Packed: 16.42 lbOperating temperature range5 to 35°COperating temperature range41 to 95°FOperating humidity range20 to 80% RHCertifications and compliancesBSMI; CB; CCC; CE; CSA; CSA-NRTL; EAC; EUP Lot-6; FCC; GEMS; HRN N N0.201; ICES; IS 1121; KC/KCC; PSB; RCM; SABS IEC 60950-1; SAS0; TUV Bauart; VCCI; ISC; EUP Lot-26; IEC 60950:1999; eStandby; MEPS (HP) UKRAINIA; ISO 9241; China CELPower supplyInput voltage 100 to 240 VACWarranty1 year parts and labour limited warranty.What's in the boxMonitor; HDMI cable; Warranty card; Power adapter; QSP; AC power cableVESA mount100 mm x 100 mm (bracket included)Product number9TQ13AS	Product dimensions	61.35 x 19.35 x 50.13 cm With stand Packed: 69.9 x 12.5 x 46.2 cm 24.16 x 2.09 x 14.43 in 24.15 x 7.62 x 19.74 in With stand
Operating temperature range41 to 95°FOperating humidity range20 to 80% RHCertifications and compliancesBSMI; CB; CCC; CE; CSA; CSA-NRTL; EAC; EUP Lot-6; FCC; GEMS; HRN N N0.201; ICES; IS 1121; KC/KCC; PSB; RCM; SABS IEC 60950-1; SA50; TUV Bauart; VCCI; ISC; EUP Lot-26; IEC 60950:1999; eStandby; MEPS (HP) UKRAINIA; ISO 9241; China CELPower supplyInput voltage 100 to 240 VACWarranty1 year parts and labour limited warranty.What's in the boxMonitor; HDMI cable; Warranty card; Power adapter; QSP; AC power cableVESA mount100 mm x 100 mm (bracket included)Product number9TQ13AS	Weight	
Operating humidity range20 to 80% RHCertifications and compliancesBSMI; CB; CCC; CE; CSA; CSA-NRTL; EAC; EUP Lot-6; FCC; GEMS; HRN N N0.201; ICES; IS 1121; KC/KCC; PSB; RCM; SABS IEC 60950-1; SAS0; TUV Bauart; VCCI; ISC; EUP Lot-26; IEC 60950:1999; eStandby; MEPS (HP) UKRAINIA; ISO 9241; China CELPower supplyInput voltage 100 to 240 VACWarranty1 year parts and labour limited warranty.What's in the boxMonitor; HDMI cable; Warranty card; Power adapter; QSP; AC power cableVESA mount100 mm x 100 mm (bracket included)Product number9TQ13AS	Operating temperature range	5 to 35°C
Certifications and compliancesBSMI; CB; CCC; CE; CSA; CSA-NRTL; EAC; EUP Lot-6; FCC; GEMS; HRN N N0.201; ICES; IS 1121; KC/KCC; PSB; RCM; SABS IEC 60950-1; SAS0; TUV Bauart; VCCI; ISC; EUP Lot-26; IEC 60950:1999; eStandby; MEPS (HP) UKRAINIA; ISO 9241; China CELPower supplyInput voltage 100 to 240 VACWarranty1 year parts and labour limited warranty.What's in the boxMonitor; HDMI cable; Warranty card; Power adapter; QSP; AC power cableVESA mount100 mm x 100 mm (bracket included)Product number9TQ13AS	Operating temperature range	41 to 95°F
Certifications and computaticesBauart; VCCI; ISC; EUP Lot-26; IEC 60950:1999; eStandby; MEPS (HP) UKRAINIA; ISO 9241; China CELPower supplyInput voltage 100 to 240 VACWarranty1 year parts and labour limited warranty.What's in the boxMonitor; HDMI cable; Warranty card; Power adapter; QSP; AC power cableVESA mount100 mm x 100 mm (bracket included)Product number9TQ13AS	Operating humidity range	20 to 80% RH
Warranty 1 year parts and labour limited warranty.   What's in the box Monitor; HDMI cable; Warranty card; Power adapter; QSP; AC power cable   VESA mount 100 mm x 100 mm (bracket included)   Product number 9TQ13AS	Certifications and compliances	
What's in the box Monitor; HDMI cable; Warranty card; Power adapter; QSP; AC power cable   VESA mount 100 mm x 100 mm (bracket included)   Product number 9TQ13AS	Power supply	Input voltage 100 to 240 VAC
VESA mount 100 mm x 100 mm (bracket included)   Product number 9TQ13AS	Warranty	1 year parts and labour limited warranty.
Product number 9TQ13AS	What's in the box	Monitor; HDMI cable; Warranty card; Power adapter; QSP; AC power cable
	VESA mount	100 mm x 100 mm (bracket included)
<b>Ordering info</b> 194721939531	Product number	9TQ13AS
	Ordering info	194721939531

© Copyright 2020 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. All other trademarks are the property of their respective owners. All performance specifications are provided by the component manufacturers. Performance specifications represent the highest specification of all HPs component manufacturers' typical level specifications for performance. Actual performance may vary either higher or lower. July 2020

